

Direct Thermal POS Receipt Printer



TYSSO®

Insist on the Best



PRP-085III



PRP-088III

PRP-085III and PRP-088III series are high-quality, low-noise thermal receipt printer speed up to 220mm/sec. and 250mm/sec. respectively, which are ideal for retail environment. In addition to the horizontal printing, PRP-088III series supports vertical and wall mount printing. The splash and dust proof design makes PRP-088III series capable of withstanding harsh environment.

FEATURES


- Halt-on protect function for overheat
- Available with serial, parallel, USB, and Ethernet interfaces
- Cash drawer connection port (RJ-11)
- Compatible with ESC/POS command sets
- Splash and dust proof design for PRP-088III series
- Support vertical printing and wall mount printing for PRP-088III series
- Drop-and-print paper installation, simple paper jam elimination
- Available with plenty of fonts
- Support OPOS driver
- Support kitchen printing and network printing
- Print and error alarm function. Paper end detection
- Built-in 128K bytes data buffer

SPECIFICATIONS


Models	PRP-085III	PRP-088III
Print Method	Thermal line printing	Thermal line printing
Print Speed	220mm/sec.	250mm/sec.
Print Resolution	576 dots/line or 512 dots/line	576 dots/line or 512 dots/line
Character Size	ANK Font Font A: 12 x 24 dots Font B: 9 x 17 dots Chinese character: 24 x 24 dots	ANK Font Font A: 12 x 24 dots Font B: 9 x 17 dots Chinese character: 24 x 24 dots
Interface	Parallel/Serial/USB/Ethernet	Parallel/Serial/USB/Ethernet
Print Width	79±0.5mm	79±0.5mm
Paper Roll Diameter	83mm	83mm
Paper Thickness	0.06~0.08mm	0.06~0.08mm
Power Supply	DC 24V / 2.5A	DC 24V / 2.5A
Driver	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista, compatible with EPSON® and SAMSUNG®	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista, compatible with EPSON® and SAMSUNG®
Auto Cutter	Full or partial	Full or partial
Reliability	100km	100km
Environment		
Operating	0°C~45°C, 10%~80%RH	0°C~45°C, 10%~80%RH
Storage	-10°C~60°C, 10%~90%RH	-10°C~60°C, 10%~90%RH
Weight	1360g (w/o cable)	1800g (w/o cable)
Dimensions (mm)	199(L) x 145(W) x 135(H)	197(L) x 140(W) x 143(H)

DIMENSIONS

PRP-085III-□-□-□



PRP-088III-□-□-□



TYSSO®
Insist on the Best

Manufacturer

FAMETECH INC.

2F, No. 165, Sec. 2, Ta-Tung Rd.,
Hsi-Chih 221, Taipei County, Taiwan
Tel : 886-2-8692-6300
Fax: 886-2-8692-6301
E-Mail: tyssso@ms6.hinet.net
URL: <http://www.famotech.com.tw>

Distributor