

Optional Palm-size and Mini-size Handheld Magstripe Portable



TYSSO®

Insist on the Best



PDC2



MPDC

Powerful and Easy-to-use

FEATURES

- Battery operated - lasts over 10,000 swipes
- Automatic shutdown for power conservation
- Data retained even if battery removed
- LED status indicators
- Reads tracks 1, 2, and 3
- Stores 3000 dual track or 1500 triple track swipes
- Required tracks configurable
- Only valid swipes are logged
- All swipes are timestamped
- Hardware password protection
- Easy-to-use download and configuration utility

SPECIFICATIONS

	<i>PCD2</i>	<i>MPDC</i>
Processor	80C31 8-bit CPU	80C31 8-bit CPU
Memory Capacity	256KB Flash	256KB Flash
Battery	9V DC Alkaline	9V DC Alkaline
Track Readability	Tracks 1&2&3 configurable	Tracks 1&2&3 configurable
Magnetic Head Life	300,000 passes minimum	300,000 passes minimum
Swipe Speed	5 to 60 inch/sec bidirectional	5 to 60 inch/sec bidirectional
Standard Compliance	ISO 7811	ISO 7811
Housing	ABS Plastic	ABS Plastic
Color	Black	Black
Dimensions	100mm(L)X33mm(W)X58 mm(H)	60mm(L)X34mm(W)X33mm(H)
Weight	131.1 grams (with battery)	50.5 grams (with battery)
Operating Temperature	0 to 45°C	0 to 45°C
Storage Temperature	-20 to 70°C	-20 to 70°C
Relative Humidity	0% to 95% (non-condensing)	0% to 95% (non-condensing)
RS-232 Cable	Stereo plug to DB9F	Stereo plug to DB9F
Operating System	Windows 98, 2000, XP	Windows 98, 2000, XP

MODELS INFORMATION

<i>Models</i>	<i>Description</i>
PDC2-M12	Palm-size with track 1&2 reading
PDC2-M33	Palm-size with track 1&2&3 reading
MPDC2-M12	Mini-size with track 1&2 reading
MPDC2-M33	Mini-size with track 1&2&3 reading



TYSSO®
Insist on the Best

Manufacturer

FAMETECH INC.

2F, No. 165, Sec. 2, Ta-Tung Rd.,
Hsi-Chih 221, Taipei Hsien, Taiwan
Tel : 886-2-8692-6300
Fax: 886-2-8692-6301
E-Mail: tyssso@ms6.hinet.net
URL: <http://www.famotech.com.tw>